

Fig.150W / Fig.150CW Single Check Valves

FEATURES & BENEFITS

- Single check valve is suitable for use in domestic water systems to outlets such as taps, mixers and showers to prevent back flow
- Supplied with compression ends complying with BS EN 1252-2 for use with R250 (half hard) copper tube or taper female threaded ends complying with BS EN 10226-2
- Spring assistance enables valve to be installed in horizontal or vertical pipework (flow in upwards direction)
- WRAS Approved for use with wholesome (potable) water to 60°C
- Shell pressure rating for Fig. 150W and Fig. 150CW is PN16 with a maximum inlet/working pressure of 10 bar

Fig.150CW



MATERIAL SPECIFICATION

Component	Material	Specification BS EN
Body	DZR Copper Alloy	BS EN 12165 CW602N
Cartridge	Acetal / Polypropylene	-
'O' ring	NBR / EPDM	-
Compression Nut	Brass	BS EN 12164 CW614N
Olive	Brass	-
Plating (Compression)	Nickel Plated	-
Plating (Threaded)	Unplated	-

PRESSURE/ TEMPERATURE RATING

Shell Pressure PN16
85°C maximum - WRAS Approved to 60°C

MAX INLET/WORKING PRESSURE

10 bar

WRAS APPROVED

10 bar

MIN OPENING PRESSURE

0.1 bar

END CONNECTIONS

Compression to BS EN 1252-2 and taper female threaded to BS EN 10226-2

APPLICATION


Water

PED


This valve is suitable for use on group 2 liquids only as defined by the Pressure Equipment Directive 2014/68/EU

DIMENSIONAL DRAWING

Compression - Fig. 150CW



Threaded - Fig. 150W



DIMENSIONS & WEIGHTS

Compression - Fig. 150CW

Nom Size	mm	15	22	28
A	mm	61	65	72
B	mm	45.5	50	56.5
C	mm	22	31.5	39
Weight (approx)	kg	0.10	0.18	0.29

Threaded - Fig. 150W

Nom Size	inch	1/2	3/4	1	1 1/4	1 1/2	2
A	inch	42	50	60	79	83.5	101
B	inch	24	32	38	46	53	64
Weight (approx)	kg	0.06	0.13	0.17	0.41	0.59	0.96

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.